



WORKING PRESSURE	200PSI
WORKING TEMP.	NBR -12° C~+82° C EPDM -35° C~+135° C
MEDIUM	W. O. G
SHELL TEST	2.07MPa
FLANGE	ASME/ANSI B16.1 C125

1	BODY	CI/DI
2	COVER	CI/DI
3	PERFORATED SCREEN	SS304
4	WIRE WOVEN SCREEN	SS304
5	O-RING	NBR/EPDM
6	KNOB BOLT	WCB
7	PLUG	WCB

SIZE	DIMENSION					SCALE:
	L1	L2	L3	L4	L5	
12x12	304.8	304.8	553	390	678	1 1/4" NPT
12x10	304.8	279.4	553	360	678	1 1/4" NPT
12x8	280	280	488	346	551	1 1/4" NPT
10x10	279.4	279.4	527	360	678	1 1/4" NPT
10x8	279.4	228.6	488	295	539	1 1/4" NPT
8x8	228.6	228.6	438	295	542	1 1/4" NPT
8x6	228.6	203.2	393	297	455	1" NPT
8x5	192	228.6	333	329	487	1" NPT
6x6	203	203	367	272	423	1" NPT
6x5	203	203	367	272	423	1" NPT
6x4	203	165	329	223	345	1" NPT
5x5	190.5	190.5	332	254	394	1" NPT
5x4	190.5	190.5	332	254	394	1" NPT
4x4	165	165	260	210	328	1" NPT
4x3	165	165	263	223	334	1" NPT
3x3	139.7	139.7	216	179	284	3/4" NPT
3x2.5	139.7	139.7	216	179	284	3/4" NPT
3x2	139.7	114.3	195	153.6	252	3/4" NPT
2.5x2.5	127	127	191	167	270	3/4" NPT
2.5x2	127	127	191	167	270	3/4" NPT
2x2	114.3	114.3	169	151	253	3/4" NPT
2X1.5	114.3	114.3	169	151	253	3/4" NPT
2X1.25	114.3	114.3	169	151	253	3/4" NPT

SIZE: PRESSURE: CLASS125 WEIGHT:

DRFTER:

MATERIAL:

CHECKED BY:

TITLE:

SUCTION DIFFUSER

SCALE:

DRAWING NO.:

DATE:

SHANGHAI FLDV VALVE & FITTING CO.,LTD
2005, Zengdai Cuike Edfice, 58 Chengqiu Road,
Pudong, Shanghai, 200135 China
TEL:+86-21-33927459 FAX:+86-21-33927465

